

HSF RoHS

REV	ECN NO	DESCRIPTION	DATE	NAME
A		NEW		

Specifications

1. Current Rating: 1Amps
2. Contact Resistance: 20mΩ
3. Insulator Resistance: 1000 Megohms min.
4. Dielectric withstanding Voltage: AC/DC 500V
5. Operating Temperature: -40℃ to +105℃
6. Contact Material: phosphor Bronze
7. Insulator Material: As follows
8. Plated: As follows

Ordering Information

L303 XX -XX 2 X X XX X




Insulation Height*Wide (H*W) Option:	NO. of Pins Per Row: 1-50P	Insulation Material Option:	Contact Plating	Serial NO.	Packing
20=2.0*2.0		1=PBT	0=0.8" Gold	01-69 (No pillars)	A=PE Bag
34=3.4*1.8		2=PPS	1=Au1" Gold	70-89 (pillars)	B=Tube
43=4.3*1.8		3=NY6T	2=Au1.5" Gold	90-99 (outside pillars)	C=Tray
		4=LCP	3=Au2" Gold		D=Reel
		5=NY66	4=Au3" Gold		
		6=Customized	5=Au5" Gold		
		7=NY46	6=Customized		
		8=NY9T	7=Gold/Tin		
			8=Tin		

Dimension antitheses list			
ITEM	PC	H	W
Standard	2.8/3.5	2.0/3.4/4.3	1.8
Alternate			

LDCONN 东莞连大精密制品有限公司
连大 DongGuan LianDa Precision Products Co., LTD

TITLE	PH1.27mm 1XNP SMT Single row Female Header	DRAWN BY	Lujunhui	18.03.30
PART NO	L303XX-XX2XXXXX	CHECKED BY		
DRAWING NO		APPROVED BY		
SCALE	1:1	UNIT	mm	PAGE 1/1 SIZE A4

STANDARD TOLERANCE (EXCEPT SPECIFIED)			
LINER		ANGLES	
.0	±0.30	0.°	±3°
.00	±0.20	.0°	±2°
.000	±0.10	.00°	±1°



PCB LAYOUT